

Description

The XT1DF24VB TVS diode is designed to replace multilayer varistors (MLVs) in portable applications such as cell phones, notebooks, and PDA's. It offers superior electrical characteristics such as low clamping voltage, low leakage current and high surge capability. It is designed to protect sensitive electronic components which are connected to power lines, from over-stress caused by ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lighting.

The XT1DF24VB is in a SOD-123FL package and will protect one bidirectional line. It may be used to provide ESD protection up to $\pm 30\text{kV}$ (Contact and air discharge) according to IEC61000-4-2, and withstand peak pulse current up to 200A (8/20 μs) according to IEC61000-4-5.


Features

- ◆ Working voltage: 24V
- ◆ SOD-123FL Package
- ◆ 6400 Watts peak pulse power ($t_p=8/20\mu\text{s}$)
- ◆ Transient protection for data lines to
IEC 61000-4-2 (ESD) $\pm 30\text{kV}$ (air),
 $\pm 30\text{kV}$ (contact)
IEC 61000-4-5 (Surge) 200A (8/20 μs)
IEC61000-4-4(EFT)40A(5/50ns)
- ◆ Low leakage current
- ◆ Low clamping voltage
- ◆ Solid-state silicon-avalanche technology


Applications

- ◆ Power lines
- ◆ Personal digital assistants (PDA's)
- ◆ Microprocessors based equipment
- ◆ Notebooks, Desktops, and Servers
- ◆ Cell phone Handsets and Accessories
- ◆ Portable Electronics
- ◆ Peripherals


<http://www.xihangsemi.com>



SOD-123FL



Circuit Diagram




Marking

Order Information

| Device | Package | Shipping |
|-----------|-----------|----------------|
| XT1DF24VB | SOD-123FL | 3000/Tape&Reel |

Definitions of electrical characteristics

| Symbol | Parameter |
|-----------|-------------------------------------|
| V_{RWM} | Reverse Stand-off Voltage |
| I_R | Reverse Leakage Current @ V_{RWM} |
| V_{BR} | Reverse Breakdown Voltage @ I_T |
| I_R | Reverse Breakdown Current |
| I_{PP} | Reverse Peak Pulse Current |
| V_C | Clamping Voltage @ I_{PP} |







Absolute Maximum Rating


| Rating | Symbol | Value | Units |
|---|-----------|--------------|-------------|
| Peak Pulse Power ($t_P = 8/20\mu S$) | P_{PK} | 6400 | W |
| Peak Pulse Current ($t_P = 8/20\mu S$) | I_{pp} | 200 | A |
| ESD according to IEC61000-4-2 air discharge | V_{ESD} | ± 30 | kV |
| ESD according to IEC61000-4-2 contact discharge | | ± 30 | kV |
| Lead Soldering Temperature | T_L | 260 (10 sec) | $^{\circ}C$ |
| Operating Temperature | T_{OP} | -55 to +125 | $^{\circ}C$ |
| Storage Temperature | T_{STG} | -55 to +150 | $^{\circ}C$ |

Electrical Characteristics ($T_a=25^{\circ}C$, unless otherwise noted)


| Parameter | Symbol | Conditions | Min. | Typ. | Max. | Units |
|---------------------------|-----------|---------------------------------|------|------|------|---------|
| Reverse Stand-off Voltage | V_{RWM} | | | | 24 | V |
| Reverse Breakdown Voltage | V_{BR} | $I_T=1mA$ | 26 | | 30 | V |
| Reverse Leakage Current | I_R | $V_{RWM}=24V$ | | | 1 | μA |
| Clamping Voltage | V_C | $I_{PP}=100A$ $t_P = 8/20\mu s$ | | | 29 | V |
| Clamping Voltage | V_C | $I_{PP}=200A$ $t_P = 8/20\mu s$ | | | 32 | V |
| Junction Capacitance | C_j | $V_R=0V$ $f = 1MHz$ | | 280 | 350 | pF |

Typical Characteristics (Ta=25°C, unless otherwise noted)



Package Outline Dimensions (SOD-123FL)



| Ref. | Dimensions | | | |
|------|-------------|------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 2.60 | 3.00 | 0.102 | 0.118 |
| B | 1.60 | 2.00 | 0.063 | 0.079 |
| C | 3.45 | 3.95 | 0.136 | 0.156 |
| D | 0.10 | 0.25 | 0.004 | 0.01 |
| E | 0.3 | 0.9 | 0.012 | 0.035 |
| F | 0.80 | 1.20 | 0.031 | 0.047 |
| G | 0.95 | 1.35 | 0.037 | 0.053 |
| J | 1.30 | | 0.051 | |
| K | | 1.70 | | 0.067 |
| L | 1.30 | | 0.051 | |

Recommend Land Pattern (Unit: mm)


Note:

This recommended land pattern is for reference purpose only.

Load With Information



NOTICE

XIHANG's products are not authorized for use as components in any life support device or systems.

XIHANG reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. XIHANG does not assume any liability arising out of the application or use of any product described herein.